

View Online at <https://aerobasegroup.com/nsn/5985-00-172-6282>

Unable To Decode:

Internal, rectangular double ridged external, rectangular

Thread Class:

2b second flange first connection facility

Thread Direction:

Right-hand second flange first connection facility

Flange Quantity:

2

Flange Inside Width:

0.689 inches first flange and 0.693 inches first flange

Flange Inside Height:

0.319 inches second flange and 0.323 inches second flange

Flange Outside Width:

1.358 inches second flange and 1.390 inches second flange

Flange Outside Height:

1.358 inches second flange and 1.390 inches second flange

Flange Depth:

0.235 inches second flange and 0.255 inches second flange

Flange Connecting Hole Diameter:

0.143 inches first flange first connection facility and 0.149 inches first flange first connection facility

Voltage Standing Wave Ratio:

1.50

Waveguide Outside Width:

0.791 inches

Thread Size:

0.138 inches second flange first connection facility

Waveguide Outside Height:

0.421 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange first connection facility

Unable To Decode:

Contact, double ridge type second flange

Special Features:

1st flange includes rf/ pressure seal w/ 0.625 in. Lg screw and lockwasher; flexible portion covered w/ molded neoprene or silicone jacket depending on use

Flexibility:

Rigid third tubing segment

Material:

Rubber chloroprene single tubing jacket or rubber silicone single tubing jacket

Surface Treatment:

Enamel third tubing segment outside surfaces

Style Designator:

Five bend type

Supplementary Features:

Marked one end w/arrow and letters outbd

Thread Series Designator:

Unc second flange first connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0