

View Online at <https://aerobasegroup.com/nsn/5985-00-172-6283>

**Unable To Decode:**

Internal, rectangular double ridged external, rectangular

**Unable To Decode:**

Seamless third tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.688 inches all flanges and 0.693 inches all flanges

**Flange Inside Height:**

0.318 inches all flanges and 0.323 inches all flanges

**Flange Outside Width:**

1.358 inches all flanges and 1.390 inches all flanges

**Flange Outside Height:**

1.358 inches all flanges and 1.390 inches all flanges

**Flange Depth:**

0.235 inches all flanges and 0.255 inches all flanges

**Flange Connecting Hole Diameter:**

0.143 inches all flanges first connection facility and 0.149 inches all flanges first connection facility

**Voltage Standing Wave Ratio:**

1.30

**Waveguide Outside Width:**

0.791 inches

**Waveguide Inside Width:**

Between 0.688 inches and 0.693 inches

**Waveguide Inside Height:**

Between 0.318 inches and 0.323 inches

**Waveguide Outside Height:**

0.421 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole all flanges first connection facility

**Unable To Decode:**

Contact, double ridge type all flanges

**Waveguide Center To Center Distance:**

10.300 inches

**Special Features:**

Flanges pressurized furnished w/ rf/ pressure seal and 0.625 in. Lg screw and lockwasher for ea mtg hole; jacket material depends on use

**Flexibility:**

Rigid third tubing segment

**Material:**

Rubber chloroprene single tubing jacket or rubber silicone single tubing jacket

**Precious Material And Location:**

Waveguide surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver second tubing segment all surfaces

**Style Designator:**

Double bend type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0