## NSN 5985-00-173-1049

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-173-1049

view Online at https://aeiobasegioup.com/hsi//3803-00-173-1049
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
3.688 inches
Overall Height:
1.875 inches
Overall Width:
1.875 inches
Distance Between Mounting Facility Centers:
1.125 inches
Operating Tempurature Range:
-20.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.30
Power Rating:
1.0 kilowatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.3
Overall Attenuation Range In Decibels:
+0.0/+100.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
10
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 hertz and 1.200 gigahertz
Overall Attenuation Accuracy In Decibels:
-5.00/+5.00
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Two position in-line

## NSN 5985-00-173-1049

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter: 0.164 inches Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A223a0