

View Online at <https://aerobasegroup.com/nsn/5985-00-173-7286>

**Application Design:**

Transmission line

**Body Material:**

Steel, qq-s-763, class 302, 303, 304, 305, 310, or 316

**Body Style:**

Round, terminal/terminals in opposite surface

**Body Surface Treatment:**

Passivated

**Overall Length:**

Between 1.344 inches and 1.469 inches

**Overall Diameter:**

0.350 inches

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Voltage Standing Wave Ratio:**

1.25 and 1.35

**Input Impedance Rating In Ohms:**

50.0

**Output Impedance Rating In Ohms:**

50.0

**Coaxial Connector Series Designation:**

Osm

**Power Rating:**

1.0 watts average and 1.0 kilowatts peak

**Rf Signal Attenuation In Decibels:**

3.0

**Voltage Standing Wave Ratio Frequency Range:**

+0.0/+4.0 gigahertz and +4.0/+12.0 gigahertz

**Attenuation Accuracy In Decibels:**

-0.30/+0.30

**Frequency Sensitivity Attenuation In Decibels:**

0.30

**Connection Type Per Function:**

Female input and male output

**Mounting Method:**

Connector

**Terminal Type And Quantity:**

2 connector

**Frequency Range:**

Between 0.000 hertz and 12.400 gigahertz

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A20000