NSN 5985-00-175-7068

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-175-7068

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 4.595 inches and 4.605 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 2.395 inches and 2.405 inches
Overall Height:
1.000 inches
Overall Width:
3.000 inches
End Application:
Radar set an/sps-40b
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Bsm and n
Power Rating:
200.0 milliwatts peak
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.4 to 66.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
5
Attenuation Per Step In Decibels:
14.6 and 15.0 and 15.0 and 21.0
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 400.000 megahertz and 450.000 megahertz
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 electronic, voltage controlled
Mounting Facility Pattern:

Four position rectangular

NSN 5985-00-175-7068

Variable Attenuator - Page 2 of 2



Mounting Facility Screw Thread Diameter:

0.164 inches

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

3 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0