NSN 5985-00-177-6258

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-177-6258

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges all connection facilities

Thread Direction:

Right-hand all flanges all connection facilities

End Application:

Radar set an/spg-51d

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.867 inches all flanges and 1.877 inches all flanges

Flange Inside Height:

0.867 inches all flanges and 0.877 inches all flanges

Flange Outside Width:

3.480 inches all flanges and 3.520 inches all flanges

Flange Outside Height:

2.480 inches all flanges and 2.520 inches all flanges

Flange Depth:

0.670 inches all flanges and 0.770 inches all flanges

Voltage Standing Wave Ratio:

1.06

Insertion Loss In Decibels:

0.05

Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

Thread Size:

0.250 inches all flanges all connection facilities

Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

Waveguide Longer Offset Distance:

8.120 inches

Flange Connecting Facility And Quantity:

8 threaded hole all flanges all connection facilities

Flange Style:

Contact type all flanges

NSN 5985-00-177-6258 Waveguide Assembly - Page 2 of 2



Waveguide Offset Distance:
7.750 inches
Flexibility:
Flexible single tubing segment
Material:
Copper alloy all tubing segment and flange
Surface Treatment:
Oxide all tubing segment and flange outside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc all flanges all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:

A073a0