## NSN 5985-00-177-7157

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-177-7157

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange all connection facilities

**Thread Direction:** 

Right-hand first flange all connection facilities

Bend Angle In Deg:

60.0 single bend e-plane

**Tubing Wall Construction Style:** 

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

0.620 inches first flange and 0.624 inches first flange

Flange Inside Height:

0.309 inches first flange and 0.313 inches first flange

Flange Outside Width:

1.297 inches first flange and 1.327 inches first flange

Flange Outside Height:

1.297 inches first flange and 1.327 inches first flange

Flange Inside Diameter:

0.985 inches first flange and 1.015 inches first flange

Flange Depth:

0.360 inches first flange and 0.390 inches first flange

**Voltage Standing Wave Ratio:** 

1.20

**Insertion Loss In Decibels:** 

0.50

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

Between 0.620 inches and 0.625 inches

Waveguide Inside Height:

Between 0.309 inches and 0.314 inches

**Waveguide Outside Height:** 

Between 0.388 inches and 0.394 inches

**Waveguide Longer Offset Distance:** 

1.520 inches

## **NSN 5985-00-177-7157** Waveguide Assembly - Page 2 of 2



Flange Connecting Facility And Quantity:
4 unthreaded hole second flange all connection facilities
Flange Style:
Choke type first flange
Waveguide Offset Distance:
0.710 inches
Flexibility:
Rigid all tubing segment
Material:
Aluminum alloy all tubing segment and flange
Surface Treatment:
Chromate all tubing segment and flange outside surfaces and enamel all tubing segment and flange outside surfaces and primer all tubing
segment and flange outside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc first flange all connection facilities
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A073a0