

View Online at <https://aerobasegroup.com/nsn/5985-00-180-4667>

**Unable To Decode:**

Internal, rectangular double ridged external, rectangular

**Unable To Decode:**

Seamless single tubing segment

**Tubing Twist Type:**

Straight twist single tubing segment

**Tubing Twist Angle In Deg:**

90.0 single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.688 inches all flanges and 0.693 inches all flanges

**Flange Inside Height:**

0.319 inches all flanges and 0.323 inches all flanges

**Flange Outside Width:**

1.358 inches all flanges and 1.390 inches all flanges

**Flange Outside Height:**

1.358 inches all flanges and 1.390 inches all flanges

**Flange Depth:**

0.235 inches all flanges and 0.255 inches all flanges

**Flange Connecting Hole Diameter:**

0.143 inches first flange first connection facility and 0.149 inches first flange first connection facility

**Voltage Standing Wave Ratio:**

1.20

**Insertion Loss In Decibels:**

0.25

**Waveguide Outside Width:**

0.791 inches

**Waveguide Inside Height:**

Between 0.688 inches and 0.693 inches

**Waveguide Outside Height:**

0.421 inches

**Waveguide Longer Offset Distance:**

15.650 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole first flange first connection facility

**Unable To Decode:**

Contact, double ridge type all flanges

**Waveguide Offset Distance:**

1.490 inches

**Special Features:**

Flanges pressurized, furnished w/ rf/ pressure seal and 0.625 in. Lg screw and lockwasher for each mtg hole

**Flexibility:**

Rigid single tubing segment

**Material:**

Aluminum alloy all flange

**Surface Treatment:**

Enamel all tubing segment and flange outside surfaces

**Style Designator:**

Bend type

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0