

View Online at <https://aerobasegroup.com/nsn/5985-00-180-4667>

Unable To Decode:

Internal, rectangular double ridged external, rectangular

Unable To Decode:

Seamless single tubing segment

Tubing Twist Type:

Straight twist single tubing segment

Tubing Twist Angle In Deg:

90.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.688 inches all flanges and 0.693 inches all flanges

Flange Inside Height:

0.319 inches all flanges and 0.323 inches all flanges

Flange Outside Width:

1.358 inches all flanges and 1.390 inches all flanges

Flange Outside Height:

1.358 inches all flanges and 1.390 inches all flanges

Flange Depth:

0.235 inches all flanges and 0.255 inches all flanges

Flange Connecting Hole Diameter:

0.143 inches first flange first connection facility and 0.149 inches first flange first connection facility

Voltage Standing Wave Ratio:

1.20

Insertion Loss In Decibels:

0.25

Waveguide Outside Width:

0.791 inches

Waveguide Inside Height:

Between 0.688 inches and 0.693 inches

Waveguide Outside Height:

0.421 inches

Waveguide Longer Offset Distance:

15.650 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange first connection facility

Unable To Decode:

Contact, double ridge type all flanges

Waveguide Offset Distance:

1.490 inches

Special Features:

Flanges pressurized, furnished w/ rf/ pressure seal and 0.625 in. Lg screw and lockwasher for each mtg hole

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy all flange

Surface Treatment:

Enamel all tubing segment and flange outside surfaces

Style Designator:

Bend type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0