

View Online at <https://aerobasegroup.com/nsn/5985-00-180-4806>

**Unable To Decode:**

Internal, rectangular double ridged external, rectangular

**Thread Class:**

2b first flange first connection facility

**Thread Direction:**

Right-hand first flange first connection facility

**Unable To Decode:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.688 inches first flange and 0.693 inches first flange

**Flange Inside Height:**

0.318 inches first flange and 0.323 inches first flange

**Flange Outside Width:**

1.358 inches first flange and 1.390 inches first flange

**Flange Outside Height:**

1.358 inches first flange and 1.390 inches first flange

**Flange Depth:**

0.235 inches first flange and 0.255 inches first flange

**Flange Connecting Hole Diameter:**

0.140 inches second flange all connection facilities and 0.154 inches second flange all connection facilities

**Voltage Standing Wave Ratio:**

1.20

**Waveguide Outside Width:**

0.791 inches

**Thread Size:**

0.138 inches first flange first connection facility

**Waveguide Inside Width:**

Between 0.688 inches and 0.693 inches

**Waveguide Inside Height:**

Between 0.318 inches and 0.323 inches

**Waveguide Outside Height:**

0.421 inches

**Flange Connecting Facility And Quantity:**

4 threaded hole first flange first connection facility

**Unable To Decode:**

Contact, double ridge type first flange

**Special Features:**

2nd flange pressurized furnished w/ rf/ pressure seal and 0.625 in. Lg screw and lockwasher for ea mtg hole

**Flexibility:**

Rigid single tubing segment

**Material:**

Aluminum alloy single tubing segment and flange

**Surface Treatment:**

Chromate single tubing segment and flange all surfaces

**Supplementary Features:**

Marked w/arrow and letters aft

**Thread Series Designator:**

Unc first flange first connection facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0