NSN 5985-00-180-4808

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-180-4808

Unable To Decode:
Internal, rectangular double ridged external, rectangular
Unable To Decode:
Seamless single tubing segment
Tubing Twist Type:
Straight twist single tubing segment
Tubing Twist Angle In Deg:
39.0 single tubing segment
Flange Quantity:
2
Flange Connecting Hole Diameter:
0.140 inches all flanges all connection facilities and 0.154 inches all flanges all connection facilities
Voltage Standing Wave Ratio:
1.50
Waveguide Outside Width:
0.791 inches
Waveguide Inside Width:
0.691 inches
Waveguide Inside Height:
0.321 inches
Waveguide Outside Height:
Waveguide Outside Height.
0.421 inches
0.421 inches
0.421 inches Flange Connecting Facility And Quantity:
0.421 inches Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities
0.421 inches Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features:
0.421 inches Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features: Includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole
0.421 inches Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features: Includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole Flexibility:
0.421 inches Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features: Includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole Flexibility: Rigid single tubing segment
0.421 inches Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features: Includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole Flexibility: Rigid single tubing segment Material:
0.421 inches Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features: Includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole Flexibility: Rigid single tubing segment Material: Aluminum alloy all flange
0.421 inches Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features: Includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole Flexibility: Rigid single tubing segment Material: Aluminum alloy all flange Surface Treatment:
O.421 inches Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features: Includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole Flexibility: Rigid single tubing segment Material: Aluminum alloy all flange Surface Treatment: Enamel single tubing segment and flange outside surfaces
Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features: Includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole Flexibility: Rigid single tubing segment Material: Aluminum alloy all flange Surface Treatment: Enamel single tubing segment and flange outside surfaces Style Designator:
0.421 inches Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features: Includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole Flexibility: Rigid single tubing segment Material: Aluminum alloy all flange Surface Treatment: Enamel single tubing segment and flange outside surfaces Style Designator: Four bend type
0.421 inches Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features: Includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole Flexibility: Rigid single tubing segment Material: Aluminum alloy all flange Surface Treatment: Enamel single tubing segment and flange outside surfaces Style Designator: Four bend type Supplementary Features:
O.421 inches Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features: Includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole Flexibility: Rigid single tubing segment Material: Aluminum alloy all flange Surface Treatment: Enamel single tubing segment and flange outside surfaces Style Designator: Four bend type Supplementary Features: One end marked w/arrow and letters fwd
O.421 inches Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features: Includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole Flexibility: Rigid single tubing segment Material: Aluminum alloy all flange Surface Treatment: Enamel single tubing segment and flange outside surfaces Style Designator: Four bend type Supplementary Features: One end marked w/arrow and letters fwd Shelf Life:
Flange Connecting Facility And Quantity: 2 unthreaded hole all flanges all connection facilities Special Features: Includes rf/pressure seal w/0.625 in. Lg screw and lockwasher for each mtg hole Flexibility: Rigid single tubing segment Material: Aluminum alloy all flange Surface Treatment: Enamel single tubing segment and flange outside surfaces Style Designator: Four bend type Supplementary Features: One end marked w/arrow and letters fwd Shelf Life: N/a

Yes - demil/mli

NSN 5985-00-180-4808 Waveguide Assembly - Page 2 of 2



Fiig:

A073a0