# NSN 5985-00-180-4828

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-180-4828

#### **Unable To Decode:**

Internal, rectangular double ridged external, rectangular

#### **Thread Class:**

2b all flanges first connection facility

#### **Thread Direction:**

Right-hand all flanges first connection facility

#### **Unable To Decode:**

Seamless second tubing segment

#### Flange Quantity:

2

### Flange Inside Width:

0.688 inches all flanges and 0.693 inches all flanges

#### Flange Inside Height:

0.318 inches all flanges and 0.323 inches all flanges

#### Flange Outside Width:

1.358 inches all flanges and 1.390 inches all flanges

# Flange Outside Height:

1.358 inches all flanges and 1.390 inches all flanges

# Flange Depth:

0.235 inches all flanges and 0.255 inches all flanges

# Flange Connecting Hole Diameter:

0.096 inches all flanges second connection facility

#### **Voltage Standing Wave Ratio:**

1.40

# **Waveguide Outside Width:**

0.791 inches

# **Thread Size:**

0.138 inches all flanges first connection facility

#### **Waveguide Inside Width:**

Between 0.688 inches and 0.693 inches

# **Waveguide Inside Height:**

Between 0.318 inches and 0.323 inches

# **Waveguide Outside Height:**

0.421 inches

# **Waveguide Longer Offset Distance:**

10.950 inches

# Flange Connecting Facility And Quantity:

4 threaded hole all flanges first connection facility

# **Unable To Decode:**

Contact, double ridge type all flanges

#### **Waveguide Offset Distance:**

1.730 inches

# NSN 5985-00-180-4828

Waveguide Assembly - Page 2 of 2



Flexibility:
Rigid second tubing segment
Material:
Aluminum alloy all flange
Surface Treatment:
Enamel second tubing segment outside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc all flanges first connection facility
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

**Fiig:** A073a0