## NSN 5985-00-181-3860

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-181-3860

A P d D t
Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.250 inches
Overall Height:
1.880 inches
Overall Width:
2.250 inches
Shaft Diameter:
0.250 inches
Shaft Length:
1.750 inches
Unthreaded Mounting Hole Diameter:
0.220 inches
Voltage Standing Wave Ratio:
1.15
Coaxial Connector Series Designation:
N
Power Rating:
1.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0 to 11.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
110
Attenuation Per Step In Decibels:
0.1
Mounting Facility Type And Quantity:
2 threaded hole and 2 unthreaded hole

Frequency Range:

Between 0.000 hertz and 500.000 megahertz

## **NSN 5985-00-181-3860** Variable Attenuator - Page 2 of 2



Overall Attenuation Accuracy In Decibels:
-0.33 to 0.33
Mounting Thread Quantity:
40 per inch
Adjustment Device Type And Quantity:
2 shaft
Mounting Facility Pattern:
our position diamond
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.112 inches
mpedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
<del>.</del>
Demilitarization:
No
Fiig:
A223a0