NSN 5985-00-184-7516

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-184-7516

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.875 inches
Overall Height:
1.687 inches
Overall Width:
4.000 inches
Shaft Length:
0.920 inches
Coaxial Connector Series Designation:
N
Power Rating:
10.0 watts average
Mounting Facility Screw Thread Series Designator:
Unf
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +0.0/+20.0
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method:
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range:
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity:
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern:
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern: Four position rectangular
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern: Four position rectangular Shaft Type:
Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern: Four position rectangular Shaft Type: Round

50.0 input-output

NSN 5985-00-184-7516

Variable Attenuator - Page 2 of 2



Terminal Type A	and Quantity	/ :
-----------------	--------------	------------

1 connector, coaxial, male and 1 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0