NSN 5985-00-184-7516

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-184-7516

| Application Design: |
|---|
| Transmission line |
| Body Style: |
| Coaxial type |
| Overall Length: |
| 5.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 4.375 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 0.875 inches |
| Overall Height: |
| 1.687 inches |
| Overall Width: |
| 4.000 inches |
| Shaft Length: |
| 0.920 inches |
| Coaxial Connector Series Designation: |
| N |
| Power Rating: |
| 10.0 watts average |
| Mounting Facility Screw Thread Series Designator: |
| |
| Unf |
| Overall Attenuation Range In Decibels: |
| |
| Overall Attenuation Range In Decibels: |
| Overall Attenuation Range In Decibels: +0.0/+20.0 |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern: |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern: Four position rectangular |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern: Four position rectangular Shaft Type: |
| Overall Attenuation Range In Decibels: +0.0/+20.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 2.000 gigahertz and 12.400 gigahertz Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft Mounting Facility Pattern: Four position rectangular Shaft Type: Round |

50.0 input-output

NSN 5985-00-184-7516

Variable Attenuator - Page 2 of 2



| Terminal Type Ar | nd Quantity: |
|------------------|--------------|
|------------------|--------------|

1 connector, coaxial, male and 1 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0