NSN 5985-00-187-1970

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-187-1970

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

4.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches

Overall Height:

2.120 inches

Overall Width:

2.240 inches

Voltage Standing Wave Ratio:

1.50

Coaxial Connector Series Designation:

Ν

Power Rating:

4.0 watts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.5

Overall Attenuation Range In Decibels:

+0.0/+30.0

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 threaded hole

Frequency Range:

Between 1.000 gigahertz and 8.000 gigahertz

Segment Attenuation Range In Decibels:

+0.00/+15.00 and +0.00/+30.00 and +0.00/+30.00

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

1 knob

Mounting Facility Pattern:

Four position rectangular

Mounting Facility Screw Thread Diameter:

0.138 inches

NSN 5985-00-187-1970

Variable Attenuator - Page 2 of 2



Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A223a0