NSN 5985-00-187-1970

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-187-1970

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
4.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.875 inches
Overall Height:
2.120 inches
Overall Width:
2.240 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
N
Power Rating:
4.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+30.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 1.000 gigahertz and 8.000 gigahertz
Segment Attenuation Range In Decibels:
+0.00/+15.00 and +0.00/+30.00 and +0.00/+30.00
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular

0.138 inches

Mounting Facility Screw Thread Diameter:

NSN 5985-00-187-1970

Variable Attenuator - Page 2 of 2



50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0