NSN 5985-00-187-7583

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-187-7583

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

2

Flange Inside Width:

3.002 inches second flange and 3.005 inches second flange

Flange Inside Height:

1.502 inches second flange and 1.505 inches second flange

Flange Outside Diameter:

5.298 inches second flange and 5.328 inches second flange

Flange Depth:

0.735 inches second flange and 0.765 inches second flange

Flange Connecting Hole Diameter:

0.257 inches second flange all connection facilities

Thready Qty Per Inch (tpi):

20 first flange all connection facilities

Maximum Operating Pressure:

5.0 pounds per square inch gage

Waveguide Outside Width:

Between 2.994 inches and 3.006 inches

Thread Size:

0.250 inches first flange all connection facilities

Waveguide Inside Width:

Between 2.834 inches and 2.846 inches

Waveguide Inside Height:

Between 1.334 inches and 1.346 inches

Waveguide Outside Height:

Between 1.494 inches and 1.506 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

1.828 feet

Flexibility:

Rigid all tubing segment

NSN 5985-00-187-7583

Waveguide Assembly - Page 2 of 2



ΝЛ	ate	ria	١.

Aluminum all tubing segment and flange

Surface Treatment:

Chromate all tubing segment and flange outside surfaces and enamel all tubing segment and flange outside surfaces and primer all tubing segment and flange outside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange all connection facilities

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A073a0