NSN 5985-00-187-7815

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-187-7815

Application Design:
Transmission line
Body Material:
Brass
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Silver plated, qq-s-365
Overall Length:
2.600 inches
Overall Diameter:
0.600 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Bnc
Power Rating:
2.0 watts average and 2.0 kilowatts peak
Rf Signal Attenuation In Decibels:
8.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.5 gigahertz
+0.0/+4.5 gigahertz Attenuation Accuracy Reference Frequency:
Attenuation Accuracy Reference Frequency:
Attenuation Accuracy Reference Frequency: 4.5 gigahertz
Attenuation Accuracy Reference Frequency: 4.5 gigahertz Attenuation Accuracy In Decibels:
Attenuation Accuracy Reference Frequency: 4.5 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60
Attenuation Accuracy Reference Frequency: 4.5 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function:
Attenuation Accuracy Reference Frequency: 4.5 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output
Attenuation Accuracy Reference Frequency: 4.5 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output Unpackaged Unit Weight:
Attenuation Accuracy Reference Frequency: 4.5 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output Unpackaged Unit Weight: 2.800 ounces
Attenuation Accuracy Reference Frequency: 4.5 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output Unpackaged Unit Weight: 2.800 ounces Mounting Method:
Attenuation Accuracy Reference Frequency: 4.5 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output Unpackaged Unit Weight: 2.800 ounces Mounting Method: Connector
Attenuation Accuracy Reference Frequency: 4.5 gigahertz Attenuation Accuracy In Decibels: -0.60/+0.60 Connection Type Per Function: Female input and male output Unpackaged Unit Weight: 2.800 ounces Mounting Method: Connector Terminal Type And Quantity:

NSN 5985-00-187-7815

Fixed Attenuator - Page 2 of 2



Precious Material And Location:
Body surfaces silver
Precious Material:
Silver
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A20000