## NSN 5985-00-188-9665

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-188-9665

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.530 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.660 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.840 inches
Overall Height:
2.500 inches
Overall Width:
0.500 inches
Unthreaded Mounting Hole Diameter:
0.090 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Osm
Power Rating:
5.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 2.000 gigahertz and 8.000 gigahertz
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:

N/a

## NSN 5985-00-188-9665

Variable Attenuator - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A223a0