NSN 5985-00-189-0599

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-189-0599

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
1.500 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.700 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.310 inches
Overall Height:
1.560 inches
Overall Width:
1.100 inches
Unthreaded Mounting Hole Diameter:
0.144 inches
Operating Tempurature Range:
+0.0/+65.0 degrees celsius
Voltage Standing Wave Ratio:
1.50
Convint Connector Series Designation
Coaxial Connector Series Designation:
Sm
-
Sm
Sm Power Rating:
Sm Power Rating: 500.0 milliwatts average
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels:
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels: 2.00
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels: 2.00 Overall Attenuation Range In Decibels:
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels: 2.00 Overall Attenuation Range In Decibels: +2.0/+22.0
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels: 2.00 Overall Attenuation Range In Decibels: +2.0/+22.0 Attenuation Accuracy Reference Frequency:
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels: 2.00 Overall Attenuation Range In Decibels: +2.0/+22.0 Attenuation Accuracy Reference Frequency: 60.0 megahertz
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels: 2.00 Overall Attenuation Range In Decibels: +2.0/+22.0 Attenuation Accuracy Reference Frequency: 60.0 megahertz Attenuation Variation Method:
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels: 2.00 Overall Attenuation Range In Decibels: +2.0/+22.0 Attenuation Accuracy Reference Frequency: 60.0 megahertz Attenuation Variation Method: Continuous
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels: 2.00 Overall Attenuation Range In Decibels: +2.0/+22.0 Attenuation Accuracy Reference Frequency: 60.0 megahertz Attenuation Variation Method: Continuous Mounting Facility Type And Quantity:
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels: 2.00 Overall Attenuation Range In Decibels: +2.0/+22.0 Attenuation Accuracy Reference Frequency: 60.0 megahertz Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels: 2.00 Overall Attenuation Range In Decibels: +2.0/+22.0 Attenuation Accuracy Reference Frequency: 60.0 megahertz Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range:
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels: 2.00 Overall Attenuation Range In Decibels: +2.0/+22.0 Attenuation Accuracy Reference Frequency: 60.0 megahertz Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 0.000 megahertz and 60.000 megahertz
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels: 2.00 Overall Attenuation Range In Decibels: +2.0/+22.0 Attenuation Accuracy Reference Frequency: 60.0 megahertz Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 0.000 megahertz and 60.000 megahertz Adjustment Device Type And Quantity:
Power Rating: 500.0 milliwatts average Insertion Loss At Minimum Attenuation In Maximum Decibels: 2.00 Overall Attenuation Range In Decibels: +2.0/+22.0 Attenuation Accuracy Reference Frequency: 60.0 megahertz Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 2 unthreaded hole Frequency Range: Between 0.000 megahertz and 60.000 megahertz Adjustment Device Type And Quantity: 1 slotted screw

95.0 input-output

NSN 5985-00-189-0599

Variable Attenuator - Page 2 of 2



	Ī	erminal	Type	And	Quantit	y:
--	---	---------	------	-----	---------	----

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0