## NSN 5985-00-191-1544

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-191-1544

Application Design:
Transmission line
Body Material:
Metal
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
1.210 inches
Overall Diameter:
0.375 inches
Operating Tempurature Range:
+0.0/+55.0 degrees celsius
Voltage Standing Wave Ratio:
1.31
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Osm
Power Rating:
500.0 milliwatts average
Rf Signal Attenuation In Decibels:
30.0
Voltage Standing Wave Ratio Frequency Range:
+9.0/+10.5 gigahertz
Attenuation Accuracy Reference Frequency:
10.5 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Female output and male input
Mounting Method:
Connector
Terminal Type And Quantity:
2 connector
Frequency Range:
Between 9.000 gigahertz and 10.500 gigahertz
Shelf Life:
N/o

N/a

## NSN 5985-00-191-1544

Fixed Attenuator - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A20000

