

View Online at <https://aerobasegroup.com/nsn/5985-00-192-2588>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Tubing Wall Construction Style:**

Convoluted single tubing segment

**Tubing Twist Type:**

Twistable single tubing segment

**Tubing Twist Angle In Deg:**

85.0 single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.253 inches all flanges

**Flange Inside Height:**

0.628 inches all flanges

**Flange Outside Width:**

1.875 inches all flanges

**Flange Outside Height:**

1.875 inches all flanges

**Flange Depth:**

0.438 inches all flanges

**Flange Connecting Hole Diameter:**

0.169 inches all flanges all connection facilities

**Voltage Standing Wave Ratio:**

1.10

**Insertion Loss In Decibels:**

0.15

**Maximum Operating Pressure:**

30.0 pounds per square inch gage

**Waveguide Outside Width:**

1.250 inches

**Waveguide Inside Width:**

1.122 inches

**Waveguide Inside Height:**

0.497 inches

**Waveguide Outside Height:**

0.625 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole all flanges all connection facilities

**Flange Style:**

Cover type all flanges

**Waveguide Length:**

3.000 feet

**Flexibility:**

Flexible single tubing segment

**Material:**

Rubber natural single tubing jacket

**Precious Material And Location:**

External surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver all tubing segment and flange outside surfaces

**Style Designator:**

Straight type

**Specification Data:**

81349-mil-w-287/3 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A073a0