

View Online at <https://aerobasegroup.com/nsn/5985-00-199-0475>

Application Design:

Transmission line

Body Material:

Steel, stainless

Body Style:

Round, terminal/terminals in opposite surface

Body Surface Treatment:

Passivated

Overall Length:

1.240 inches

Overall Diameter:

0.385 inches

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Voltage Standing Wave Ratio:

1.15

Input Impedance Rating In Ohms:

50.0

Output Impedance Rating In Ohms:

50.0

Coaxial Connector Series Designation:

Osm

Power Rating:

1.0 watts average and 1.0 kilowatts peak

Rf Signal Attenuation In Decibels:

10.0

Voltage Standing Wave Ratio Frequency Range:

+0.0/+5.0 gigahertz

Attenuation Accuracy Reference Frequency:

5.0 gigahertz

Attenuation Accuracy In Decibels:

-0.60/+0.60

Connection Type Per Function:

Female output and male input

Unpackaged Unit Weight:

0.300 ounces

Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 5.000 gigahertz

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A20000