## NSN 5985-00-201-3680

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-201-3680

Application Design:
Audio
Body Style:
Cylindrical w/side terminals
Overall Length:
3.531 inches
Overall Width:
1.625 inches
Body Diameter:
1.625 inches
Shaft Diameter:
0.250 inches
Bushing Length:
0.375 inches
Shaft Length:
2.000 inches
Body Length:
1.125 inches
Schematic Diagram Designator:
Unbalanced "Ir"
Power Rating:
4.0 watts average
Mounting Facility Screw Thread Series Designator:
Unef
Overall Attenuation Range In Decibels:
+0.0/+20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
1 threaded bushing
Frequency Range:
Between 0.000 kilohertz and 20.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-1.50/+1.50
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
2 shaft
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.375 inches

## NSN 5985-00-201-3680

Variable Attenuator - Page 2 of 2



Termina	I Type	And (	Quantit	٧.
	11 1 1 1 1 1 1	Allu '	wuanni	ν.

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0