NSN 5985-00-203-5869

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-203-5869

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Convolute single tubing segment

Flange Quantity:

2

Flange Inside Width:

3.002 inches all flanges

Flange Inside Height:

1.505 inches all flanges

Flange Outside Width:

4.500 inches all flanges

Flange Outside Height:

3.000 inches all flanges

Flange Depth:

0.500 inches all flanges

Flange Connecting Hole Diameter:

0.263 inches all flanges single connection facility

Voltage Standing Wave Ratio:

1.08

Maximum Operating Pressure:

35.0 pounds per square inch gage

Waveguide Outside Width:

Between 2.994 inches and 3.006 inches

Waveguide Inside Width:

Between 2.834 inches and 2.846 inches

Waveguide Inside Height:

Between 1.334 inches and 1.346 inches

Waveguide Outside Height:

Between 1.494 inches and 1.506 inches

Flange Connecting Facility And Quantity:

10 unthreaded hole all flanges single connection facility

Flange Style:

Contact type all flanges

Waveguide Length:

6.000 inches

Flexibility:

Flexible single tubing segment

Material:

Any acceptable all flange

Surface Treatment:

Oxide film all tubing segment and flange inside surfaces

NSN 5985-00-203-5869

Waveguide Assembly - Page 2 of 2



Style Designator:
Straight type
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A073a0