## NSN 5985-00-203-5871

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-203-5871

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b all flanges single connection facility

**Thread Direction:** 

Right-hand all flanges single connection facility

Bend Angle In Deg:

90.0 single bend e-plane

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

3.002 inches all flanges

Flange Inside Height:

1.502 inches all flanges

Flange Outside Width:

3.844 inches all flanges

Flange Outside Height:

2.344 inches all flanges

Flange Depth:

0.375 inches all flanges

**Voltage Standing Wave Ratio:** 

1.08

**Insertion Loss In Decibels:** 

0.02

**Maximum Operating Pressure:** 

5.0 pounds per square inch gage

**Waveguide Outside Width:** 

3.000 inches

**Thread Size:** 

0.164 inches all flanges single connection facility

Waveguide Inside Width:

2.840 inches

**Waveguide Inside Height:** 

1.340 inches

**Waveguide Outside Height:** 

1.500 inches

**Waveguide Longer Offset Distance:** 

3.440 inches

Flange Connecting Facility And Quantity:

10 threaded hole all flanges single connection facility

## **NSN 5985-00-203-5871** Waveguide Assembly - Page 2 of 2



| Flange Style:  |
|--|
| Contact type all flanges                                 |
| Waveguide Offset Distance:                               |
| 2.440 inches   |
| Flexibility:   |
| Flexible single tubing segment                           |
| Material:  |
| Aluminum single tubing segment                           |
| Surface Treatment:                                       |
| Oxide film all tubing segment and flange inside surfaces |
| Style Designator:  |
| Elbow type   |
| Thread Series Designator:                                |
| Unc all flanges single connection facility               |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Yes - demil/mli  |
| Fiig:  |
| A073a0   |
|  |