# NSN 5985-00-205-8853

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-205-8853

#### **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### Thread Class:

2b first flange all connection facilities

## **Thread Direction:**

Right-hand first flange all connection facilities

#### Bend Angle In Deg:

90.0 single bend h-plane

#### **Tubing Wall Construction Style:**

Seamless single tubing segment

# Flange Quantity:

# 2

Flange Inside Width:

1.003 inches second flange and 1.006 inches second flange

#### Flange Inside Height:

0.503 inches second flange and 0.506 inches second flange

#### Flange Outside Width:

1.610 inches second flange and 1.640 inches second flange

# Flange Outside Height:

1.610 inches first flange and 1.640 inches first flange

#### Flange Inside Diameter:

1.406 inches first flange and 1.437 inches first flange

#### Flange Depth:

0.423 inches second flange and 0.453 inches second flange

## Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

#### Voltage Standing Wave Ratio:

1.10

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

#### Waveguide Outside Width:

Between 0.996 inches and 1.004 inches

#### Thread Size:

0.164 inches first flange all connection facilities

#### Waveguide Inside Width:

Between 0.896 inches and 0.904 inches

## Waveguide Inside Height:

Between 0.396 inches and 0.404 inches

#### Waveguide Outside Height:

Between 0.496 inches and 0.504 inches

# Waveguide Longer Offset Distance:

1.370 inches

# NSN 5985-00-205-8853

Waveguide Assembly - Page 2 of 2



# Flange Connecting Facility And Quantity:

4 unthreaded hole second flange all connection facilities

#### Flange Style:

Cover type second flange

# Waveguide Offset Distance:

1.370 inches

Flexibility:

Rigid single tubing segment

Material:

Copper alloy all tubing segment and flange

#### Surface Treatment:

Oxide film all tubing segment and flange inside surfaces

#### Style Designator:

Corner type

#### **Thread Series Designator:**

Unc first flange all connection facilities

#### **Specification Data:**

81349-mil-w-3970/16 government specification

#### **Fsc Application Data:**

Antennas, waveguides, and related equipment

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

### Fiig:

A073a0