

View Online at <https://aerobasegroup.com/nsn/5985-00-220-3965>

Application Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

6.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.812 inches

Overall Height:

2.190 inches

Overall Width:

4.310 inches

Unthreaded Mounting Hole Diameter:

0.170 inches

Operating Temperature Range:

+0.0/+70.0 degrees celsius

Voltage Standing Wave Ratio:

1.20 and 1.40

Coaxial Connector Series Designation:

N

Power Rating:

500.0 milliwatts average

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.1

Overall Attenuation Range In Decibels:

+0.0/+135.0

Attenuation Accuracy Reference Frequency:

250.0 megahertz

Attenuation Variation Method:

Continuous

Mounting Facility Type And Quantity:

4 unthreaded hole

Frequency Range:

Between 0.000 hertz and 1.300 gigahertz

Overall Attenuation Accuracy In Decibels:

-0.50/+0.50

Adjustment Device Type And Quantity:

1 motor

Mounting Facility Pattern:

Four position rectangular

Impedance Rating In Ohms:

50.0 input-output

Terminal Type And Quantity:

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0