

View Online at <https://aerobasegroup.com/nsn/5985-00-224-3581>

Thread Class:

2b mounting facility hole

Body Style:

Irregular

Overall Length:

3.062 inches

Overall Height:

1.312 inches

Overall Width:

2.000 inches

Frequency Rating:

0.0 megahertz and 30.0 megahertz single frequency insertion loss reference

Switch Type:

Transfer

Longest Horizontal Distance Between Mounting Centers:

1.250 inches single mounting facility pattern

Shortest Horizontal Distance Between Mounting Centers:

0.781 inches single mounting facility pattern

Intermediate Horizontal Distance Between Mounting Centers:

1.250 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

0.937 inches single mounting facility pattern

Voltage Standing Wave Ratio:

1.03 single

Insertion Loss In Decibels:

0.10 single

Coaxial Connector Series Designation:

Bnc

Connector End Design:

Female

Rf Power Handling Capability:

2.0 kilowatts peak single

Minimum Crosstalk Rating In Decibels:

50.0 single

Actuator Operating Method:

Relay

Actuator Voltage In Volts:

26.0

Switch Operation Sequence:

Makes before breaks

Switching Time:

20.0 milliseconds

Coupling Position Quantity:

3

Mounting Facility Type And Quantity:

4 threaded hole

Thread Size:

0.138 inches mounting facility hole

Mounting Facility Pattern:

Four position parallelogram single mounting facility pattern

Precious Material And Location:

External body surfaces silver

Precious Material:

Silver

Surface Treatment:

Silver body outside surfaces

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

5 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0