

View Online at <https://aerobasegroup.com/nsn/5985-00-224-3581>

**Thread Class:**

2b mounting facility hole

**Body Style:**

Irregular

**Overall Length:**

3.062 inches

**Overall Height:**

1.312 inches

**Overall Width:**

2.000 inches

**Frequency Rating:**

0.0 megahertz and 30.0 megahertz single frequency insertion loss reference

**Switch Type:**

Transfer

**Longest Horizontal Distance Between Mounting Centers:**

1.250 inches single mounting facility pattern

**Shortest Horizontal Distance Between Mounting Centers:**

0.781 inches single mounting facility pattern

**Intermediate Horizontal Distance Between Mounting Centers:**

1.250 inches single mounting facility pattern

**Longest Vertical Distance Between Mounting Centers:**

0.937 inches single mounting facility pattern

**Voltage Standing Wave Ratio:**

1.03 single

**Insertion Loss In Decibels:**

0.10 single

**Coaxial Connector Series Designation:**

Bnc

**Connector End Design:**

Female

**Rf Power Handling Capability:**

2.0 kilowatts peak single

**Minimum Crosstalk Rating In Decibels:**

50.0 single

**Actuator Operating Method:**

Relay

**Actuator Voltage In Volts:**

26.0

**Switch Operation Sequence:**

Makes before breaks

**Switching Time:**

20.0 milliseconds

**Coupling Position Quantity:**

3

**Mounting Facility Type And Quantity:**

4 threaded hole

**Thread Size:**

0.138 inches mounting facility hole

**Mounting Facility Pattern:**

Four position parallelogram single mounting facility pattern

**Precious Material And Location:**

External body surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver body outside surfaces

**Thread Series Designator:**

Unc mounting facility hole

**Terminal Type And Quantity:**

5 receptacle, coaxial

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A158a0