## NSN 5985-00-226-5512

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-226-5512

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Thread Class:** 

2b first flange single connection facility

**Thread Direction:** 

Right-hand first flange single connection facility

Bend Angle In Deg:

90.0 first bend e-plane

**Tubing Wall Construction Style:** 

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.384 inches second flange and 1.389 inches second flange

Flange Inside Height:

0.759 inches second flange and 0.764 inches second flange

Flange Outside Width:

1.875 inches second flange

Flange Outside Height:

1.875 inches second flange

Flange Depth:

0.625 inches first flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility and 0.172 inches second flange single connection facility

**Voltage Standing Wave Ratio:** 

1.12

**Waveguide Outside Width:** 

Between 1.373 inches and 1.383 inches

**Thread Size:** 

0.164 inches first flange single connection facility

Waveguide Inside Width:

Between 1.119 inches and 1.125 inches

**Waveguide Inside Height:** 

Between 0.748 inches and 0.758 inches

**Waveguide Outside Height:** 

Between 0.494 inches and 0.500 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole second flange single connection facility

Flange Style:

Cover type second flange

Flexibility:

Rigid single tubing segment

## NSN 5985-00-226-5512

Waveguide Assembly - Page 2 of 2



|     |      |      | -   |
|-----|------|------|-----|
| ΝЛ  | late | ria  |     |
| IVI | ale  | :110 | ı . |

Copper alloy all tubing segment and flange

**Surface Treatment:** 

Enamel all tubing segment and flange outside surfaces

**Thread Series Designator:** 

Unc first flange single connection facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0