# NSN 5985-00-226-5514

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-226-5514

## **Cross Sectional Shape:**

Internal, rectangular external, rectangular

#### Bend Angle In Deg:

180.0 single bend e-plane

## **Tubing Wall Construction Style:**

Seamless single tubing segment

## Flange Quantity:

2

#### Flange Inside Width:

1.118 inches all flanges and 1.126 inches all flanges

#### Flange Inside Height:

0.493 inches all flanges and 0.501 inches all flanges

#### Flange Outside Width:

1.875 inches all flanges

Flange Outside Height:

1.875 inches all flanges

#### Flange Depth:

0.625 inches all flanges

## Flange Connecting Hole Diameter:

0.185 inches all flanges single connection facility and 0.193 inches all flanges single connection facility

## Voltage Standing Wave Ratio:

1.04

#### Maximum Operating Pressure:

15.0 pounds per square inch gage

#### Waveguide Outside Width:

Between 1.373 inches and 1.383 inches

#### Waveguide Inside Width:

Between 1.119 inches and 1.125 inches

#### Waveguide Inside Height:

Between 0.494 inches and 0.500 inches

#### Waveguide Outside Height:

Between 0.748 inches and 0.758 inches

## Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges single connection facility

#### Flange Style:

Choke type all flanges

## Waveguide Leg Length:

1.600 inches

## Waveguide Longer Leg Length:

1.600 inches

#### Waveguide Center To Center Distance:

Between 3.980 inches and 4.020 inches

# NSN 5985-00-226-5514

Waveguide Assembly - Page 2 of 2



Waveguide Height:

3.997 inches

Flexibility:

Rigid single tubing segment

Material:

Copper alloy all tubing segment and flange

Surface Treatment:

Paint all tubing segment and flange outside surfaces

## Style Designator:

U-bend type

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

## Fiig:

A073a0