NSN 5985-00-226-5624

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-226-5624

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b all flanges single connection facility

Thread Direction:

Right-hand all flanges single connection facility

Tubing Wall Construction Style:

Seamless all tubing segment

Flange Quantity:

4

Flange Inside Width:

1.118 inches all flanges and 1.126 inches all flanges

Flange Inside Height:

0.493 inches all flanges and 0.501 inches all flanges

Flange Outside Width:

1.875 inches all flanges

Flange Outside Height:

1.875 inches all flanges

Flange Depth:

0.625 inches all flanges

Voltage Standing Wave Ratio:

1.08

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.373 inches and 1.383 inches

Thread Size:

0.164 inches all flanges single connection facility

Waveguide Inside Width:

Between 1.119 inches and 1.125 inches

Waveguide Inside Height:

Between 0.494 inches and 0.500 inches

Waveguide Outside Height:

Between 0.748 inches and 0.758 inches

Flange Connecting Facility And Quantity:

4 threaded hole all flanges single connection facility

Flange Style:

Choke type all flanges

Special Features:

C/o two waveguide sections, one straight section 12.250 in. Lg and one bend section with two easy bends 13.000 in. O/a lg

Flexibility:

Rigid all tubing segment

NSN 5985-00-226-5624

Waveguide Assembly - Page 2 of 2



Material:

Copper alloy all tubing segment and flange

Surface Treatment:

Paint single tubing segment outside surfaces

Thread Series Designator:

Unc all flanges single connection facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0