NSN 5985-00-229-2929

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-229-2929 **Application Design:** Waveguide **Body Material:** Any acceptable **Body Style:** Rectangular, terminal/terminals on opposite surfaces **Overall Length:** 10.800 inches **Center To Center Distance Between Mounting Facilities Parallel To Length:** 1.220 inches **Overall Height:** Between 1.610 inches and 1.640 inches **Overall Width:** Between 1.610 inches and 1.640 inches **Mounting Hole/stud Quantity: Inside Width:** 0.622 inches **Unthreaded Mounting Hole Diameter:** Between 0.1695 inches and 0.1715 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.280 inches **Inside Height:** 0.310 inches **Voltage Standing Wave Ratio:** 1.15 **Rf Signal Attenuation In Decibels: Voltage Standing Wave Ratio Frequency Range:** +8.2/+12.4 gigahertz **Waveguide Flange Type: Waveguide Flange Designation:** Ug-39/u **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Waveguide Designation:** Rg-52/u **Mounting Method:** Terminal w/mounting holes

2 flange

Terminal Type And Quantity:

NSN 5985-00-229-2929

Fixed Attenuator - Page 2 of 2



Fr	ea	uen	cv	Ra	na	e:

Between 8.200 gigahertz and 12.400 gigahertz

Specification Data:

18876-7913122 manufacturers specification control

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A20000