Radio Frequency Transmission Line Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-229-4542

| Thread Class: |
|--|
| 2b mounting facility hole |
| Body Style: |
| Rectangular |
| Overall Width: |
| 1.500 inches |
| Frequency Rating: |
| 0.000 gigahertz and 1.213 gigahertz single frequency rf power handling |
| Switch Type: |
| Nontransfer |
| Distance Between Mounting Facility Centers: |
| 1.000 inches single mounting facility pattern |
| Voltage Standing Wave Ratio: |
| 1.20 single |
| Insertion Loss In Decibels: |
| 0.15 single |
| Coaxial Connector Series Designation: |
| Tnc |
| Connector End Design: |
| Female |
| Minimum Crosstalk Rating In Decibels: |
| 70.0 single |
| Actuator Operating Method: |
| Manual |
| Switch Operation Sequence: |
| Makes before breaks |
| Pole Quantity: |
| 6 |
| Throw Quantity: |
| 2 |
| Coupling Position Quantity: |
| 6 |
| Mounting Facility Type And Quantity: |
| 2 threaded hole |
| Thread Size: |
| 0.164 inches mounting facility hole |
| Mounting Facility Pattern: |
| Two position in-line single mounting facility pattern |
| Material: |
| Metal body |
| Precious Material And Location: |
| Serous cold |

Screws gold

NSN 5985-00-229-4542

Radio Frequency Transmission Line Switch - Page 2 of 2



Precious Material:

Gold

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

6 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0