## NSN 5985-00-229-8000

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-229-8000

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
6.968 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
5.250 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.750 inches
Overall Height:
2.000 inches
Overall Width:
1.750 inches
Scale Linearity:
Linear
Operating Tempurature Range:
-25.0/+150.0 degrees fahrenheit
Coaxial Connector Series Designation:
N
Power Rating:
100.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0/+41.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
41
Attenuation Per Step In Decibels:
1.0
Mounting Facility Type And Quantity:
4 threaded hole
Frequency Range:
Between 0.000 megahertz and 500.000 megahertz
Overall Attenuation Accuracy In Decibels:
-2.05/+2.05
Mounting Thread Quantity:

32 per inch

## NSN 5985-00-229-8000

Variable Attenuator - Page 2 of 2



## Adjustment Device Type And Quantity: 6 lever Mounting Facility Pattern: Four position rectangular Mounting Facility Screw Thread Diameter: 0.138 inches Impedance Rating In Ohms: 50.0 input-output Terminal Type And Quantity: 2 connector, coaxial, female Shelf Life: N/a Unit Of Measure: --Demilitarization:

Yes - demil/mli

Fiig: A223a0