

View Online at https://aerobasegroup.com/nsn/5985-00-229-8016

#### **Thread Class:**

2b mounting facility stud

#### **Body Style:**

Rectangular

# **Overall Length:**

2.032 inches

#### **Overall Height:**

2.500 inches

#### **Overall Width:**

2.094 inches

#### **Frequency Rating:**

0.0 gigahertz and 3.0 gigahertz single frequency voltage standing wave ratio

#### Switch Type:

Nontransfer

#### **Operating Tempurature Range:**

-25.0/+140.0 degrees fahrenheit

# Voltage Standing Wave Ratio:

1.60 single

#### Insertion Loss In Decibels:

0.25 single

# **Coaxial Connector Series Designation:**

Bnc

#### **Connector End Design:**

Female

#### **Rf Power Handling Capability:**

2.0 kilowatts peak single

#### Minimum Crosstalk Rating In Decibels:

85.0 single

#### **Actuator Operating Method:**

Relay

#### Actuator Voltage In Volts:

Between 19.0 and 32.0

#### **Switch Operation Sequence:**

Breaks before makes

#### Switching Time:

15.0 milliseconds

#### Switch Return Mechanism Type:

Latching

## **Pole Quantity:**

1

#### **Throw Quantity:**

2

# NSN 5985-00-229-8016

Radio Frequency Transmission Line Switch - Page 2 of 2



**Coupling Position Quantity:** 

3

# Mounting Facility Type And Quantity:

3 threaded stud

# Thread Size:

0.138 inches mounting facility stud

## Material:

Steel body

# Surface Treatment:

Chromium body outside surfaces

# **Thread Series Designator:**

Unc mounting facility stud

# Terminal Type And Quantity:

3 receptacle, coaxial

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A158a0