## NSN 5985-00-230-5160

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-230-5160

Application Design:
Audio
Body Style:
Cylindrical w/rear terminals
Overall Length:
0.875 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.375 inches
Body Length:
0.500 inches
Overall Diameter:
2.750 inches
Schematic Diagram Designator:
Balanced "h" bridged
Distance Between Mounting Facility Centers:
1.500 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Power Rating:
0.5 watts average
Mounting Facility Screw Thread Series Designator:
Unef
Overall Attenuation Range In Decibels:
+0.0/+60.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
30
Attenuation Per Step In Decibels:
2.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 0.000 kilohertz and 20.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-1.50/+1.50
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:

1 shaft

## NSN 5985-00-230-5160

Variable Attenuator - Page 2 of 2



Mounting Facility Pattern:
Two position in-line
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.375 inches
Impedance Rating In Ohms:
600.0 input-output
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A223a0