## NSN 5985-00-230-5166

Variable Attenuator - Page 1 of 2

**Application Design:** 

Audio

**Body Style:** 



View Online at https://aerobasegroup.com/nsn/5985-00-230-5166

Cylindrical w/rear terminals
Overall Length:
3.938 inches
Shaft Diameter:
0.250 inches
Shaft Length:
0.938 inches
Body Length:
3.000 inches
Overall Diameter:
2.781 inches
Schematic Diagram Designator:
Balanced "h"
Distance Between Mounting Facility Centers:
1.500 inches
Power Rating:
2.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Overall Attenuation Range In Decibels:
+0.0/+70.0
Attenuation Variation Method:
Stepped
Step Position Quantity:
7
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
2 threaded hole
Frequency Range:
Between 200.000 hertz and 35.000 kilohertz
Overall Attenuation Accuracy In Decibels:
-0.35/+0.35
Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Two position in-line

## NSN 5985-00-230-5166

Variable Attenuator - Page 2 of 2



Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.164 inches
Impedance Rating In Ohms:
600.0 input-output
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A223a0