NSN 5985-00-231-3694

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-231-3694

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.310 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.880 inches
Overall Height:
2.060 inches
Overall Width:
1.480 inches
Voltage Standing Wave Ratio:
1.50
Coaxial Connector Series Designation:
Bnc
Power Rating:
1.0 watts average
Mounting Facility Screw Thread Series Designator:
Unc
Unc Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels:
Overall Attenuation Range In Decibels: +0.0/+25.0
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method:
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method: Continuous
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range:
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 60.000 megahertz
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 60.000 megahertz Overall Attenuation Accuracy In Decibels:
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 60.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 60.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity:
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 60.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity: 40 per inch
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 60.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity: 40 per inch Adjustment Device Type And Quantity:
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 60.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity: 40 per inch Adjustment Device Type And Quantity: 1 slotted screw
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 60.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity: 40 per inch Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern:
Overall Attenuation Range In Decibels: +0.0/+25.0 Attenuation Variation Method: Continuous Mounting Facility Type And Quantity: 4 threaded hole Frequency Range: Between 0.000 megahertz and 60.000 megahertz Overall Attenuation Accuracy In Decibels: -0.50/+0.50 Mounting Thread Quantity: 40 per inch Adjustment Device Type And Quantity: 1 slotted screw Mounting Facility Pattern: Four position rectangular

50.0 input-output

NSN 5985-00-231-3694

Variable Attenuator - Page 2 of 2



Terminal Type Ar	nd Quantity:
------------------	--------------

2 connector, coaxial, female

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0