NSN 5985-00-231-8897

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-231-8897

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
2.250 inches
Bolt Circle Diameter:
2.000 inches
Overall Height:
3.750 inches
Overall Width:
2.750 inches
Scale Linearity:
Nonlinear
Scale Division Quantity:
12
Shaft Diameter:
Between 0.245 inches and 0.255 inches
Shaft Length:
0.562 inches
Operating Tempurature Range:
+0.0/+70.0 degrees celsius
Voltage Standing Wave Ratio:
1.05
Coaxial Connector Series Designation:
Bnc
Power Rating:
250.0 milliwatts average
Mounting Facility Screw Thread Series Designator:
Unc
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.1
Overall Attenuation Range In Decibels:
+0.0/+9.7
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
3 threaded hole
Frequency Range:
Between 0.000 megahertz and 100.000 megahertz
Overall Attenuation Accuracy In Decibels:

-0.10/+0.10

NSN 5985-00-231-8897

Variable Attenuator - Page 2 of 2



Mounting Thread Quantity:
32 per inch
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Three position circular
Shaft Type:
Round
Mounting Facility Screw Thread Diameter:
0.138 inches
Impedance Rating In Ohms:
75.0 input-output
Terminal Type And Quantity:
2 connector, coaxial, female
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A223a0