NSN 5985-00-233-2208

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-233-2208
Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Anodized
Overall Length:
2.500 inches
Overall Diameter:
0.562 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.25
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
N
Power Rating:
25.0 watts average
Rf Signal Attenuation In Decibels:
30.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+4.0 gigahertz
Attenuation Accuracy Reference Frequency:
4.0 gigahertz
Attenuation Accuracy In Decibels:
-1.30/+1.30
Connection Type Per Function:
Female output and male input
Mounting Method:

Connector

Terminal Type And Quantity:

2 connector

Frequency Range:

Between 0.000 hertz and 4.000 gigahertz

Precious Material And Location:

Connector surfaces silver

NSN 5985-00-233-2208

Fixed Attenuator - Page 2 of 2



Precious Material:
Silver
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A20000