

View Online at <https://aerobasegroup.com/nsn/5985-00-233-6730>

Body Style:

Irregular

Overall Length:

1.097 inches

Overall Height:

0.810 inches

Overall Width:

0.440 inches

Frequency Rating:

0.0 megahertz and 500.0 megahertz single frequency operating
0.0 megahertz and 500.0 megahertz single frequency voltage standing wave ratio
0.0 megahertz and 500.0 megahertz single frequency insertion loss reference
0.0 megahertz and 500.0 megahertz single frequency crosstalk reference

Switch Type:

Transfer

Distance Between Mounting Facility Centers:

0.400 inches single mounting facility pattern

Voltage Standing Wave Ratio:

1.20 single

Insertion Loss In Decibels:

0.60 single

Minimum Crosstalk Rating In Decibels:

50.0 single

Actuator Operating Method:

Relay

Actuator Voltage In Volts:

26.5 and 32.0

Switch Operation Sequence:

Breaks before makes

Switching Time:

4.0 milliseconds

Rf Maximum Voltage Rating:

1.0 kilovolts rms

Coupling Position Quantity:

2

Mounting Facility Type And Quantity:

2 slot

Mounting Facility Pattern:

Two position in-line single mounting facility pattern

Special Features:

8.500 in. Lg rg-316/u coaxial cable attached to pins 1 and 6

Material:

Nickel body

Terminal Type And Quantity:

2 wire lead and 6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A158a0