

View Online at <https://aerobasegroup.com/nsn/5985-00-233-6740>

**Body Style:**

Irregular

**Overall Length:**

1.097 inches

**Overall Height:**

0.810 inches

**Overall Width:**

0.440 inches

**Frequency Rating:**

0.0 megahertz and 500.0 megahertz single frequency operating  
0.0 megahertz and 500.0 megahertz single frequency voltage standing wave ratio  
0.0 megahertz and 500.0 megahertz single frequency insertion loss reference  
0.0 megahertz and 500.0 megahertz single frequency crosstalk reference

**Switch Type:**

Transfer

**Voltage Standing Wave Ratio:**

1.20 single

**Insertion Loss In Decibels:**

0.60 single

**Minimum Crosstalk Rating In Decibels:**

50.0 single

**Actuator Operating Method:**

Relay

**Actuator Current Type And Rating In Amps:**

1.0 dc

**Actuator Voltage In Volts:**

26.5 and 32.0

**Switch Operation Sequence:**

Breaks before makes

**Switching Time:**

4.0 milliseconds

**Rf Maximum Voltage Rating:**

1.0 kilovolts rms

**Coupling Position Quantity:**

2

**Mounting Facility Type And Quantity:**

2 slot

**Special Features:**

8.500 in. Lg rg-316/u coaxial cable attached to pins 1, 2, and 6

**Material:**

Nickel alloy body

**Terminal Type And Quantity:**

3 wire lead and 5 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A158a0