

View Online at <https://aerobasegroup.com/nsn/5985-00-234-6750>

**Thread Class:**

2b second flange all connection facilities

**Thread Direction:**

Right-hand second flange all connection facilities

**End Application:**

Landing control central an/spn-10 and an/spn-42

**Tubing Wall Construction Style:**

Seamless single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

0.2786 inches second flange and 0.2814 inches second flange

**Flange Inside Height:**

0.1386 inches second flange and 0.1414 inches second flange

**Flange Outside Width:**

0.735 inches second flange and 0.765 inches second flange

**Flange Outside Height:**

0.735 inches second flange and 0.765 inches second flange

**Flange Inside Diameter:**

0.485 inches second flange and 0.515 inches second flange

**Flange Depth:**

0.195 inches second flange and 0.225 inches second flange

**Flange Connecting Hole Diameter:**

0.125 inches first flange all connection facilities

**Voltage Standing Wave Ratio:**

1.15

**Insertion Loss In Decibels:**

0.30

**Thready Qty Per Inch (tpi):**

32 second flange all connection facilities

**Thread Size:**

0.112 inches second flange all connection facilities

**Flange Connecting Facility And Quantity:**

6 unthreaded hole first flange all connection facilities

**Flange Style:**

Choke type first flange

**Special Features:**

Frequency range 33.200 ghz porm 300 ghz; temperature range minus 28 to plus 85 degrees c

**Precious Material:**

Silver and gold

**Surface Treatment:**

Primer all tubing segment and flange outside surfaces and enamel all tubing segment and flange outside surfaces

**Style Designator:**

Waveguide to waveguide

**Thread Series Designator:**

Unc second flange all connection facilities

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A073a0