NSN 5985-00-238-9301

Variable Attenuator - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5985-00-238-9301

A	Application Design:
	Vaveguide
	Body Style:
	Vaveguide type
	Overall Length:
	5.500 inches
C	Center To Center Distance Between Mounting Facilities Parallel To Length:
1	.280 inches
C	Center To Center Distance Between Mounting Facilities Parallel To Width:
1	.220 inches
C	Dverall Height:
3	3.125 inches
c	Overall Width:
5	5.625 inches
ι	Inthreaded Mounting Hole Diameter:
0	0.170 inches
F	Power Rating:
1	.0 watts average
C	Overall Attenuation Range In Decibels:
+	-2.0/+40.0
A	Attenuation Variation Method:
C	Continuous
N	Nounting Facility Type And Quantity:
4	terminal w/mounting holes
F	Frequency Range:
E	Between 8.500 gigahertz and 9.600 gigahertz
C	Overall Attenuation Accuracy In Decibels:
-2	2.00/+2.00
N	Nounting Facility Pattern:
F	Four position rectangular
Т	Ferminal Type And Quantity:
5	5 flange
F	Sc Application Data:
Т	Fest set, radar
S	Shelf Life:
Ν	l/a
ι	Jnit Of Measure:
	-
C	Demilitarization:
Ν	ю
F	iig:
Α	A223a0