NSN 5985-00-239-1974

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-239-1974

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange single connection facility

Thread Direction:

Right-hand first flange single connection facility

Bend Angle In Deg:

45.0 single bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.148 inches second flange

Flange Inside Height:

0.638 inches second flange

Flange Outside Width:

1.688 inches second flange

Flange Outside Height:

1.688 inches second flange

Flange Depth:

0.500 inches second flange

Flange Connecting Hole Diameter:

0.169 inches second flange single connection facility

Voltage Standing Wave Ratio:

1.05

Insertion Loss In Decibels:

0.10

Thready Qty Per Inch (tpi):

32 first flange single connection facility

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

1.148 inches

Thread Size:

0.164 inches first flange single connection facility

Waveguide Inside Width:

1.020 inches

Waveguide Inside Height:

0.510 inches

Waveguide Outside Height:

0.638 inches

NSN 5985-00-239-1974 Waveguide Assembly - Page 2 of 2



Waveguide Longer Offset Distance:
2.440 inches
Flange Connecting Facility And Quantity:
4 unthreaded hole second flange single connection facility
Flange Style:
Cover type second flange
Waveguide Offset Distance:
1.130 inches
Flexibility:
Rigid single tubing segment
Material:
Aluminum alloy 6061 all tubing segment
Surface Treatment:
Enamel all tubing segment outside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc first flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A073a0