NSN 5985-00-239-6119

Material:

Aluminum body

Radio Frequency Transmission Line Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-239-6119

Body Style:
Irregular
Overall Length:
3.438 inches
Frequency Rating:
0.0 gigahertz and 2.0 gigahertz single frequency operating 0.0 gigahertz and 2.0 gigahertz single frequency rf power handling 0.0
gigahertz and 2.0 gigahertz single frequency voltage standing wave ratio0.0 gigahertz and 2.0 gigahertz single frequency insertion loss
reference0.0 gigahertz and 2.0 gigahertz single frequency crosstalk reference
Overall Diameter:
2.531 inches
Switch Type:
Nontransfer
Distance Between Mounting Facility Centers:
1.125 inches single mounting facility pattern
Voltage Standing Wave Ratio:
1.30 single
Insertion Loss In Decibels:
0.10 single
Coaxial Connector Series Designation:
Bnc
Connector End Design:
Female
Rf Power Handling Capability:
100.0 watts average single
Minimum Crosstalk Rating In Decibels:
80.0 single
Actuator Operating Method:
Manual
Switch Operation Sequence:
Breaks before makes
Pole Quantity:
2
Throw Quantity:
2
Coupling Position Quantity:
6
Mounting Facility Type And Quantity:
2 threaded hole
Thread Size:
0.164 inches mounting facility hole
Mounting Facility Pattern:
Two position in-line single mounting facility pattern

NSN 5985-00-239-6119

Radio Frequency Transmission Line Switch - Page 2 of 2



Precious Material And Location:
Connector surfaces silver
Precious Material:
Silver
Surface Treatment:
Anodize body outside surfaces
Thread Series Designator:
Unc mounting facility hole
Terminal Type And Quantity:
6 receptacle, coaxial
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A158a0