## NSN 5985-00-239-6120

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-239-6120

Application Design:
Transmission line
Body Style:
Cylindrical w/adjustment knob
Overall Length:
2.469 inches
Overall Diameter:
2.500 inches
Voltage Standing Wave Ratio:
1.30
Coaxial Connector Series Designation:
Bnc
Power Rating:
1.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.2
Overall Attenuation Range In Decibels:
+0.0/+50.0
Attenuation Accuracy Reference Frequency:
400.0 megahertz
Attenuation Variation Method:
Stepped
Step Position Quantity:
5
Attenuation Per Step In Decibels:
10.0
Mounting Facility Type And Quantity:
2 terminal
Frequency Range:
Between 0.000 hertz and 900.000 megahertz
Overall Attenuation Accuracy In Decibels:
-2.50/+2.50
Adjustment Device Type And Quantity:
1 knob
Impedance Rating In Ohms:
50.0 input-output
Special Features:
Equipped w/dial and indicator bracket
Terminal Type And Quantity:
2 connector, coaxial, male
Shelf Life:
N/a

## NSN 5985-00-239-6120

Variable Attenuator - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A223a0